

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A communication terminal device provided with a function of rejecting receipt of messages from communication partners other than communication partners previously registered in receipt-allowed communication partner registration table,

said communication terminal device comprising:

a receipt rejecting communication control medium collecting communication control information in connection with a communication relating to a message arrival from a communication partner not registered in said receipt-allowed communication partner registration table and storing said collected communication control information in a signal-receiving rejecting communication control information storage medium;

a communication control list creating medium creating a list of image information on the basis of said communication control information stored in said signal-receiving rejecting communication control information storage medium; and

a list outputting medium visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

2. (currently amended) A method of controlling a communication terminal device

provided with a function of rejecting receipt of messages from communication partners other than communication partners previously registered in a receipt-allowed communication partner registration table,

said method of controlling the communication terminal device comprising:

collecting communication control information in connection with a communication relating to a message arrival, from a communication partner not registered in said receipt-allowed communication partner registration table and storing said collected communication control information in a signal-receiving rejecting communication control information storage medium;

creating a list of image information on the basis of said communication control information stored in said signal-receiving rejecting communication control information storage medium; and

visibly outputting said created list of image information,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

3. (currently amended) A communication terminal device provided with a function of rejecting receipt of messages from communication partners other than communication partner previously registered in a receipt-allowed communication partner registration table, said communication terminal device comprising:

a normal communication control medium collecting communication control information in connection with a communication relating to receipt of a message from a communication partner registered in a transmission-allowed communication partner registration table or said

receipt-allowed communication partner registration table, and storing said collected communication control information in a normal communication control information storage medium;

a receipt-rejected communication control medium collecting communication control information in connection with a communication relating to a message arrival from a communication partner not registered in said receipt-allowed communication partner registration table and storing said collected communication control information in a receipt-rejected communication control information storage medium;

a communication control list creating medium creating a communication control list such that lists image information based on the communication control information respectively stored in said normal communication control information storage medium and said receipt-rejected communication control information storage medium, wherein the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table can be discriminated from the communication control information in connection with the communication relating to the receipt of the messages from the communication partner registered in a transmission-allowed communication registering table; and

a list outputting medium visibly outputting the list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

4. (currently amended) A method of controlling a communication terminal device provided with a function of rejecting receipt of messages from communication partners other than communication partners previously registered in a receipt-allowed communication partner registration table,

said method of controlling the communication terminal device comprising:

collecting communication control information in connection with communication relating to receipt of a message from the communication partner registered in a transmission-allowed communication partner registration table or said receipt-allowed communication partner registration table, and storing said collected communication control information in a normal communication control information storage medium;

collecting said communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registration table;

storing said corrected communication control information in a receipt-rejected communication control information storage medium;

creating a communication control list that lists image information based on the communication control information respectively stored in said normal communication control information storage medium and said receipt-rejected communication control information storage medium, wherein the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table can be discriminated from the communication control information in connection with the communication relating to the receipt of the messages from the communication partner registered in the transmission-allowed communication registering table; and

visibly outputting the communication control list of image information,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

5. (original) The communication terminal device as defined in claim 1, wherein said communication control information collected by said receipt rejecting communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes communication partner discriminating information notified at the time of the message arrival.

6. (original) The communication terminal device as defined in claim 3,
wherein said communication control information collected by said receipt rejecting communication control medium and stored in said receipt-rejected communication control information memorizing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes communication partner discriminating information notified at the time of the message arrival.

7. (original) The method of controlling the communication terminal device as defined in claim 2,

wherein said communication control information stored in said signal-receiving rejecting

communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the communication partner discriminating information notified at the time of the message arrival.

8. (original) The method of controlling the communication terminal device as defined in claim 4,

wherein said communication control information stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes communication partner discriminating information notified at the time of the message arrival.

9. (original) The communication terminal device as defined in claim 1, further comprising:

a time counting medium for counting a present date and time,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

10. (original) The communication terminal device as defined in claim 3, further

comprising:

a time counting medium for counting a present date and time,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

11. (original) The communication terminal device as defined in claim 5, further comprising:

a time counting medium for counting a present date and time

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

12. (original) The communication terminal device as defined in claim 6, further comprising:

a time counting medium for counting the present date and time

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control

information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

13. (original) The communication terminal device as defined in claim 2,
wherein the communication control information stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes date-and-time information at the time of the message arrival.

14. (original) The communication terminal device as defined in claim 4,
wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes date-and-time information at the time of the message arrival.

15. (original) The communication terminal device as defined in claim 7,
wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes date-and-time information at the time of the message arrival.

16. (original) The communication terminal device as defined in claim 8, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes date-and-time information at the time of the message arrival.

17. (currently amended) A facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than communication partners previously registered in a receipt-allowed communication partner registering table,

said facsimile device provided with a receipt-rejecting function comprising:

a receipt-rejected communication control medium collecting the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, and storing said collected communication control information in a receipt-rejected communication control information storage medium;

a communication control list creating medium creating a list of image information on the basis of the communication control information stored in said receipt-rejected communication control information storage medium; and

a list outputting medium visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication.

18. (currently amended) A method of controlling a facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than a communication partner previously registered in a receipt-allowed communication partner registering table,

said method of controlling the facsimile device provided with a receipt-rejecting function comprising the steps of:

collecting communication control information in connection with the communication relating to message arrival from a communication partner not registered in said receipt-allowed communication partner registering table;

storing said collected communication control information in a receipt-rejected communication control information storage medium;

creating a list of image information on the basis of the communication control information stored in said receipt-rejected communication control information storage medium;
and

visibly outputting said created list of image information,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication.

19. (currently amended) A facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than a communication partners previously registered in a receipt-allowed communication partner registering table,

said facsimile device provided with a receipt-rejecting function comprising:

a normal communication control medium collecting communication control information in connection with the communication relating to a message receipt from a registered communication partner registered in a transmission-allowed communication partner registering table or in said receipt-allowed communication partner registering table and storing said collected communication control information in said normal communication control information storage medium;

a receipt-rejected communication control medium collecting the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, and storing said collected communication control information in a receipt-rejected communication control information storage medium;

a communication control list creating medium creating a list of image information on the basis of the communication control information respectively stored in said normal communication control information storage medium and said receipt-rejected communication control information storage medium and creating communication control information in connection with the communication relating, to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, such that both of said communication control information can be discriminated from the communication control information in connection with the communication relating to the message receipt from the communication partner registered in the transmission communication partner registering table

or in said receipt-allowed communication partner registering table; and

a list outputting medium visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication.

20. (currently amended) A method of controlling a facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than communication partners previously registered in a receipt-allowed communication partner registering table,

said method of controlling the facsimile device comprising the steps of:

collecting communication control information in connection with communication relating to the message receipt from the communication partner registered in the transmission-allowed communication partner registering table or in said receipt-allowed communication partner registering table;

storing said collected communication control information in said normal communication control information storage medium;

collecting the communication control information in connection with communication relating to the message arrival from communication partner not registered in said receipt-allowed communication partner registering table;

storing said collected communication control information in said receipt-rejected communication control information storing medium;

creating the list of image information on the basis of the communication control information respectively stored in said normal communication control information storing medium and said receipt-rejected communication control information storing medium and creating the communication control information in connection with communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, such that both of said communication control information can be discriminated from the communication control information in connection with the communication relating to the message receipt from the communication partner registered in the transmission communication partner registering table or in said receipt-allowed communication partner registering table; and

visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication.

21. (original) The facsimile device provided with a receipt-rejecting function as defined in claim 17,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

22. (original) The facsimile device provided with a receipt-rejecting function as defined in claim 19,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

23. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

24. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

25. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18,

wherein the communication control information memorized in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

26. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20,

wherein the communication control information stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

27. (original) The facsimile device provided with a receipt-rejecting functions as defined in claim 17,

wherein said facsimile device further comprises a time counting medium for counting the present date and time; and

wherein the communication control information collected by said receipt-rejected communication control medium and storing in said receipt-rejected communication control information memorizing medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

28. (original) The facsimile device provided with a receipt-rejecting functions as defined in claim 19,

wherein said facsimile device further comprises a time counting medium for counting the present date and time; and

wherein the communication control information collected by said receipt-rejected communication control medium and storing in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

29. (original) The facsimile device provided with a receipt-rejecting, functions as defined in claim 21,

wherein said facsimile device further comprises a time counting medium for counting the present date and time; and

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

30. (original) The facsimile device provided with a receipt-rejecting functions as defined in claim 22,

wherein said facsimile device further comprises a time counting medium for counting the present date and time; and

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

31. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

32. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

33. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 23 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

34. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 24 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

35. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out at the time of the message arrival.

36. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, so as to include the date-and-time information read out at the time of the message arrival.

37. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 23 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out at the time of the message arrival.

38. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 24 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out at the time of the message arrival.

39. (currently amended) A communication terminal device provided with a function of rejecting the receipt of messages from communication partners excluding a communication partner previously registered in a receipt-allowed communication partner registration table,

said communication terminal device comprising:

receipt rejecting communication control means collecting communication control information in connection with the communication relating to the message arrival from a communication partner not registered in said receipt-allowed communication partner registration

table, and storing said collected communication control information in signal-receiving rejecting communication control information storing means;

communication control list creating means creating a list of image information on the basis of said communication control information stored in said signal-receiving rejecting communication control information storing means; and

list outputting means visibly outputting said list of image information created by said communication control list creating means,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

40. (currently amended) A communication terminal device provided with a function of rejecting the receipt of messages from communication partners excluding a communication partner previously registered in a receipt-allowed communication partner registration table,

said communication terminal device comprising:

normal communication control means collecting communication control information in connection with the communication relating to the receipt of the message from the communication partner registered in a transmission-allowed communication partner registration table or said receipt-allowed communication partner registration table, and storing said collected communication control information in said normal communication control information storing means;

receipt-rejected communication control means collecting said communication control information in connection with the communication relating to the message arrival from a

communication partner not registered in said receipt-allowed communication partner registration table and storing said corrected communication control information in a receipt-rejected communication control information memorizing means;

communication control list creating means creating said communication control list such that a list of image information based on the communication control information respectively stored in said normal communication control information storing means and said receipt-rejected communication control information storing means, and the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table can be discriminated from the communication control information in connection with the communication relating to the receipt of the messages from the communication partner registered in a transmission-allowed communication registering table; and

list outputting means visibly outputting the list of image information created by said communication control list creating means,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication.

41. (currently amended) A facsimile device provided with a receipt-rejected function of rejecting the message receipt from a communication partner excluding communication partners previously registered in a receipt-allowed communication partner registered in a receipt-allowed communication partner registering table, said facsimile device provided with a receipt-rejecting function comprising:

receipt-rejected communication control means collecting the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, and storing said collected communication control information in said receipt-rejected communication control information storing means;

communication control list creating means creating a list of image information on the basis of the communication control information stored in said receipt-rejected communication control information storing means; and

list outputting means visibly outputting said list of image information created by said communication control list creating means,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a message receiving process is not performed by said facsimile device for the receipt-rejected communication.

42. (currently amended) A facsimile device provided with a receipt-rejected function of rejecting the message receipt from a communication partner excluding communication partners previously registered in a receipt-allowed communication partner registering table,

said facsimile device provided with a receipt-rejecting function comprising:

normal communication control means collecting the communication control information in connection with the communication relating to the message receipt from the communication partner registered in the transmission-allowed communication partner registering table or in said receipt-allowed communication partner registering table and storing said collected communication control information in said normal communication control information storing

means;

receipt-rejected communication control means collecting the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, and storing said collected communication control information in said receipt-rejected communication control information storing means;

communication control list creating means creating the list of image information on the basis of the communication control information respectively memorized in said normal communication control information storing means and said receipt-rejected communication control information storing means and creating the communication control information in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, such that both of said communication control information can be discriminated from the communication control information in connection with the communication relating to the message receipt from the communication partner registered in the transmission communication partner registering table or in said receipt-allowed communication partner registering table; and

list outputting means visibly outputting said list of image information created by said communication control list creating means,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a message receiving process is not performed by said facsimile device for the receipt-rejected communication.

43. (previously presented) The communication terminal device of claim 1, wherein said

receipt rejecting communication control medium rejects said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table.

44. (new) The communication terminal device of claim 1, wherein said list of image information created by said communication control list creating medium includes communication control information for a plurality of communications.